

On the web server configuration for OAIC website (oaic.gov.au), the LogFormat configurations are:

```
=====
CustomLog logs/access_logs/oaic.gov.au.log anchorremoteip
ErrorLog logs/error_logs/oaic.gov.au.log
=====
```

"anchorremoteip" is a custom LogFormat, and is set to be:

```
LogFormat "%a %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-Agent}i\" %Dus"
anchorremoteip
```

The variables are defined in the Apache webserver documentation [0] and refer to:

%a	-	Client IP address of the request
%l	-	Remote logname (from identd, if supplied). This will return a dash unless mod_ident is present and IdentityCheck is set On.
%u	-	Remote user if the request was authenticated. May be bogus if return status (%s) is 401 (unauthorized).
%t	-	Time the request was received, in the format [18/Sep/2011:19:18:28 -0400].
%r	-	First line of request. Looks something like "GET /assets/hero-images/angelene-falk.jpg HTTP/1.1"
%>s	-	Final status code
%b	-	Size of response in bytes, excluding HTTP headers
%{Referer}i	-	The contents of the Referer Header in the HTTP request.
%{User-Agent}i	-	The contents of the User Agent Header in the HTTP request.
%Dus	-	The time taken to serve the request, in microseconds, followed by the characters 'us'